



UNIVERSITI PUTRA MALAYSIA

**MODELING OF SPECIFIC ABSORPTION RATE DISTRIBUTION IN
HUMAN HEAD DUE TO FAR FIELD ELECTROMAGNETIC WAVE
RADIATION OF 900 MHZ AND 1800 MHZ USING THE METHOD OF
MOMENT**

NOR AZAH BINTI ABDUL AZIZ.

ITMA 2005 4

DEDICATION

To my beloved late dad, mum, families and hubby.

Abstract of thesis presented to the Senate of Universiti Putra Malaysia in fulfilment of the requirements for the degree of Master of Science

MODELING OF SPESIFIC ABSORPTION RATE DISTRIBUTION IN HUMAN HEAD DUE TO FAR FIELD ELECTROMAGNETIC WAVE RADIATION OF 900 MHz AND 1800 MHz USING THE METHOD OF MOMENT

By

NOR AZAH BINTI ABDUL AZIZ

June 2005

Chairperson : Zulkifly Abbas, PhD

Institute : Advanced Technology

In this study, a method of moment has been used to determine the induced electric field and specific absorption rate (SAR) distribution inside the human head due to far field electromagnetic wave radiation. Homogeneous and three layered spherical models were used to simulate a head of a two year old child at 900 MHz and 1800 MHz. In the models, the antenna was placed at 30 cm away from the head. The head was represented by 680 cells, suitable when using PC with Pentium IV processor and 512 MB DDR RAM memory. The method of moments (MOM) was employed to calculate the induced electric field which in turn can obtain the absorbed power, P_{abs} ; localized SAR, SAR ; and averaged SAR, SAR_{avg} . The results of the calculated SAR were presented for the far field case. For both homogeneous and three layered models, the value of SAR were found higher at frequency of 1800 MHz than 900 MHz. At both frequencies, the three

layered models have shown lower values of SAR. The results have shown the maximum absorbed power, localized SAR and averaged SAR are found in a homogeneous model at 1800 MHz, followed by three layered model at 1800 MHz, homogeneous model at 900 MHz and three layered model at 900 MHz. The averaged SAR for all models were in range 0.003 W/kg to 0.005 W/kg, which were still far behind the safety limit 0.08 W/kg averaged over 1 g of tissue. It was found that the behaviour of the localized SAR distribution were not uniform inside the head. It might be due to multiple reflection and absorption in the head. Besides, the incident electric field calculated in many angles might also contribute to the non-uniformity.

Abstrak tesis yang dikemukakan kepada Senat Universiti Putra Malaysia sebagai memenuhi keperluan untuk ijazah Master Sains

**PERMODELAN TABURAN KADAR PENYERAPAN SPESIFIK DI DALAM
KEPALA MANUSIA YANG TERHASIL DARI RADIASI GELOMBANG
ELECTROMAGNET PADA 900 MHz ADAN 1800 MHz DENGAN
MENGUNAKAN KAEDAH MOMEN**

Oleh

NOR AZAH BINTI ABDUL AZIZ

Jun 2005

Pengerusi : Zulkifly Abbas, PhD

Institut : Teknologi Maju

Dalam kajian ini, kaedah momen telah digunakan untuk menentukan medan elektrik dan taburan kadar penyerapan spesifik (SAR) di dalam kepala manusia yang terhasil dari medan jauh radiasi gelombang elektromagnet. Model-model sfera yang sejenis dan tiga lapis digunakan untuk menyerupai kepala seorang budak yang berumur dua tahun pada frekuensi 900 MHz dan 1800 MHz. Dalam model itu, antenna diletakkan pada jarak 30 cm dari kepala. Kepala itu terdiri dari sebanyak 680 sel yang sesuai dengan penggunaan komputer peribadi dengan pemproses Pentium IV dan memori 512 MB DDR RAM. Kaedah momen (MOM) digunakan untuk mengira medan elektrik yang terhasil seterusnya dapat mengetahui kuasa serapan, P_{abs} ; SAR setempat, SAR ; and SAR purata, SAR_{avg} . Keputusan bagi SAR yang dikira disampaikan untuk kes medan jauh. Bagi

kedua-dua model sejenis dan tiga lapis, nilai SAR didapati lebih tinggi pada frekuensi 1800 MHz dari 900 MHz. Pada kedua-dua frekuensi, model tiga lapis telah menunjukkan bacaan yang lebih rendah. Keputusan telah menunjukkan kuasa serapan maksimum, P_{abs} ; SAR setempat maksimum, SAR ; and SAR purata maksimum, SAR_{avg} ditemui dalam model sejenis pada 1800 MHz, diikuti dengan model tiga lapis pada 1800 MHz, model sejenis padat 900 MHz dan model tiga jenis pada 900 MHz. Bagi kesemua model, SAR purata berada dalam julat 0.003 W/kg hingga 0.005 W/kg, di mana nilainya masih jauh dari had keselamatan 0.08 W/kg yang dipuratakan bagi 1 g tisu. Didapati juga, sifat taburan SAR setempat di dalam kepala adalah tidak seragam. Keadaan demikian mungkin disebabkan oleh pantulan dan penyerapan dari pelbagai sudut dalam kepala. Selain itu, medan elektrik insiden yang dikira dari pelbagai sudut juga boleh menyumbang kepada ketidakseragaman taburan tersebut.

ACKNOWLEDGEMENT

First and foremost, I would like to express my deepest gratitude to chairman of the supervisory committee, Dr Zulkifly Abbas, for his advices, guidance and encouragement during these two years. I wish to extend my appreciation to the members of the supervisory committee; Associates Professor Dr Hishamuddin Zainuddin and Professor Dr Mohd Yusof Sulaiman for their advices.

My sincere thanks should be given to You Kok Yoew who always give his hand during my work; Theoretical Studies Laboratory Staff and Students especially En.Ali and Nurisya for their efforts to provide the best facilities ever, all Dr. Zulkifly Abbas's students for sharing information and moments, all staff in ITMA and FSAS. To Dibah and her husband, I will never forget your kindheartedness. Not forgotten, to my sponsor, Ministry of Science, Technology and Innovation for giving me the NSF scholarship.

To my dearest mum, late dad and my big family members, I will always adore your love, sacrifices and supports till what I am now. Last but not least, my greatest love and thanks to my husband who always gives never ending love and encouragement.

I certify that an Examination Committee met on 7th June 2005 to conduct the final examination of Nor Azah binti Abdul Aziz on her Master of Science thesis entitled "Modeling of Specific Absorption Rate Distribution in Human Head Due to Far Field Electromagnetic Wave Radiation of 900 MHz and 1800 MHz Using the Method of Moment" in accordance with Universiti Pertanian Malaysia (Higher Degree) Act 1980 and Universiti Pertanian Malaysia (Higher Degree) Regulations 1981. The Committee recommends that the candidate be awarded the relevant degree. Members of the Examination Committee are as follows:

Zaidan Abdul Wahab, PhD

Associate Professor
Faculty of Science
Universiti Putra Malaysia
(Chairman)

Abd Halim Shaari, PhD

Professor
Faculty of Science
Universiti Putra Malaysia
(Internal Examiner)

Jumiah Hassan, PhD

Lecturer
Faculty of Science
Universiti Putra Malaysia
(Internal Examiner)

Kaharudin Dimiyati, PhD

Associate Professor
Faculty of Engineering
Universiti Malaya
(External Examiner)



GULAM RUSUL RAHMAT ALI, PhD

Professor/Deputy Dean
School of Graduate Studies
Universiti Putra Malaysia

Date: 21 JUL 2005

This thesis submitted to the Senate of Universiti Putra Malaysia has been accepted as fulfilment of the requirement for the degree of Master of Science. The members of the Supervisory Committee are as follows:

ZULKIFLY ABBAS, PhD


Lecturer
Faculty of Science
Universiti Putra Malaysia
(Chairman)

MOHD. YUSOF SULAIMAN, PhD

Professor
Faculty of Science
Universiti Putra Malaysia
(Member)

HISHAMUDDIN ZAINUDDIN, PhD

Associate Professor
Faculty of Science
Universiti Putra Malaysia
(Member)




AINI IDERIS, PhD
Professor / Dean
School of Graduate Studies
Universiti Putra Malaysia

Date: 11 AUG 2005

DECLARATION

I hereby declare that the thesis is based on my original work except for quotations and citations which have been duly acknowledged. I also declare that it has not been previously or concurrently submitted for any other degree at UPM or other institutions.



NOR AZAH BINTI ABDUL AZIZ

Date: 18.07.05

TABLE OF CONTENTS

	Page
DEDICATION	ii
ABSTRACT	iii
ABSTRAK	v
ACKNOWLEDGEMENT	vii
APPROVALS	viii
DECLARATION	x
LIST OF TABLES	xiii
LIST OF FIGURES	xiv
LIST OF ABBREVIATIONS	xvi

CHAPTER

1. INTRODUCTION	1
1.1 Introduction	1
1.2 Cellular Communication and Interaction in Biological System	1
1.3 Review of the Numerical Techniques	3
1.4 Dose Rate and Safety Standard	5
1.4.1 Dose Rate	6
1.4.2 Exposure Limit	8
1.5 Objectives	9
1.6 Scope of Work	10
2. ELECTROMAGNETIC ABSORPTION IN HUMAN BODY	11
2.1 Introduction	11
2.2 Dielectric Properties of Biological Tissues	12
2.3 Maxwell's Equations	14
2.4 Plane Wave Propagation	16
2.4.1 Plane Wave	16
2.4.2 Field Properties	18
2.4.3 Wave Impedance	20
2.4.4 Near Field	21
2.4.5 Far Field	21
2.4.6 Boundary Condition	23
2.5 Electromagnetic Behaviour as a Function of Size and Wavelength	24
2.6 Waves In Lossy Medium	26
2.7 Energy Absorption and Specific Absorption Rate	27



3. METHOD OF MOMENT	31
3.1 Introduction	31
3.2 Derivation of Equivalent Current Densities	32
3.3 Derivation of Integral Equation	35
3.4 Transformation of the Integral Equation into a Matrix Equation (Discretization)	39
3.5 Evaluation of the Matrix Elements	42
3.6 Solution of the Matrix Equation	44
 4. METHODOLOGY AND COMPUTATIONS	 45
4.1 Introduction	45
4.2 Description of the Implemented Models	46
4.2.1 Homogeneous Model	48
4.2.2 Three Layered Head Model	49
4.3 Numerical Modeling	51
4.3.1 Method of Moment using FORTRAN	51
4.3.2 Program Description	56
4.3.3 Input File	57
4.3.4 Program Procedure and Flow Diagram	58
 5. RESULTS AND DISCUSSIONS	 69
5.1 Introduction	69
5.2 Simulation Results	69
5.2 Discussions	79
 6. CONCLUSIONS AND RECOMMENDATIONS	 83
6.1 Conclusions	83
6.2 Contributions	84
6.3 Recommendations for Future Work	85
 REFERENCES	 87
APPENDICES	92
APPENDIX A: Program Listing	92
APPENDIX B: Input Files	98
APPENDIX C: Output Files	100
BIODATA OF THE AUTHOR	101

LIST OF TABLES

Table	Page
1.1 SAR limit proposed in the USA (ANSI 1992), Europe (CENELEC 1995) and Japan (TTC/MPT 1990) for the frequency range of mobile communication (40 MHz to 6 GHz)	7
4.1 Material properties of homogeneous spherical head at 900 MHz and 1800 MHz.	48
4.2 Material properties of three layered spherical head at 900 MHz.	50
4.3 Material properties of three layered spherical head at 1800 MHz.	50
4.4 Cases of study according to frequency, type and distance.	52
4.5 Description of parameters of main program and subroutine used in FORTRAN algorithm.	57
5.1 Total power absorbed, peak absorbed power, peak localized SAR and peak average localized SAR (1g) in the head model.	78

LIST OF FIGURES

Figure	Page
2.1 A plane wave.	16
2.2 Illustration of interfaces.	20
2.3 Illustration of far field.	22
2.4 Illustration of boundary conditions between two materials.	23
2.4 The wavelength is large compared to the size of the device.	25
2.5 The wavelength and the size of the device are comparable.	25
2.6 The wavelength is small compared with the size of the device.	26
3.1 A biological body illuminated by a plane electromagnetic wave.	33
4.1 Head of a two year old child exposed at 30 cm from cellular phone.	47
4.2 Plane wave incident upon homogeneous spherical head.	49
4.3 Plane wave incident upon three layered spherical head.	50
4.4 Geometry of a three layered head model at (a) $y = 0.5\text{cm}$ (b) $y = 1.5\text{cm}$ (c) $y = 2.5\text{cm}$ (d) $y = 3.5\text{cm}$ (e) $y = 4.5\text{cm}$ (f) $y = 5.5\text{cm}$.	55
4.5 A flow diagram in FORTRAN algorithm.	68
5.1 The distributions of localized SAR along the x -, y - and z - axis of Case H30_900.	71
5.2 The distributions of localized SAR along the x -, y - and z - axis of Case H30_1800.	71
5.3 The distributions of localized SAR along the x -, y - and z - axis of Case 3L30_900.	72
5.4 The distributions of localized SAR along the x -, y - and z - axis of Case 3L30_1800.	72
5.5 Distributions of localized SAR along x -axis.	75

5.6	Distributions of localized SAR along y -axis.	76
5.7	Distributions of localized SAR along z -axis.	76
5.8	Comparison results for cases H30_900, H30_1800, 3L30_900 and 3L30_1800.	78

LIST OF ABBREVIATIONS

IEEE	-	Institute of Electric and Electronic Engineers.
RF	-	Radiofrequency.
ANSI	-	American National Standard Institute.
NCRP	-	National Council on Radiation Protection and Measurement.
IRPA	-	International Radiation Protection Radiation
CENELEC	-	European Committee for Electrotechnical Standardization
TIE	-	Tensor Integral Equation.
IE	-	Integral Equation.
EBCM	-	Extended Boundary Condition Method.
IEBCM	-	Interactive Extended Boundary Condition Method.
FDTD	-	Finite Different Time Domain.
MOM	-	Method of Moment.
FEM	-	Finite Element Method.
PDE	-	partial differential equation.
FORTTRAN	-	Formula translation.
DDR RAM	-	Double data rate random access memory.
PC	-	personal computer.
SAR	-	Specific Absorption Rate.
SAR	-	localized SAR.
SAR_{avg}	-	averaged SAR.
SAR_{max}	-	maximum localized SAR.

$SAR_{av\ max}$	-	maximum averaged SAR.
P_{abs}	-	absorbed power.
P_{max}	-	maximum absorbed power.
dP	-	incremental electromagnetic power.
dm	-	incremental mass.
dV	-	volume element.
f	-	frequency.
π	-	pi = 3.141592654
j	-	imaginary part.
ϵ_0	-	free space permittivity.
μ_0	-	free space permeability.
ϵ_r	-	relative permittivity.
μ_r	-	relative permeability.
ϵ	-	permittivity.
μ	-	permeability
ϵ_c	-	complex relative permittivity.
μ_c	-	complex relative permeability.
ϵ'	-	real part of the complex relative permittivity.
ϵ''	-	imaginary part of the complex relative permittivity.
μ'	-	real part of the complex relative permeability.
μ''	-	imaginary part of the complex relative permeability.
ω	-	angular frequency.

t	-	elapsed time.
ρ	-	tissue density.
σ	-	tissue conductivity.
σ_{eff}	-	effective conductivity.
E_{rms}	-	root-mean-square (rms) value of the magnitude \vec{E} .
\vec{E}^i	-	incident electric field.
\vec{E}^s	-	scattered electric field.
\vec{E}	-	electric field intensity or induced electric field.
\vec{H}^i	-	incident magnetic field.
\vec{H}^s	-	scattered magnetic field.
\vec{H}	-	magnetic field intensity or induced electric field.
\vec{D}	-	electric flux density.
\vec{B}	-	magnetic flux density.
\vec{J}	-	electric current density (general).
ρ_f	-	electric charge density.
$\vec{\nabla}$	-	del operator.
\vec{J}_e	-	electric current density.
\vec{J}_m	-	magnetic current density.
\vec{J}_{eq}	-	equivalent current density in free space.
\vec{r}	-	field point.
\vec{r}'	-	source point.
τ	-	array storing value

\vec{A}	-	magnetic vector potential.
\vec{G}	-	vector Green's function.
G_0	-	free space scalar Green's function.
\vec{G}_0	-	free space dyadic Green's function.
\vec{G}_{0x}	-	free space vector Green's function with a source pointed in the x direction.
\vec{G}_{0y}	-	free space vector Green's function with a source pointed in the y direction.
\vec{G}_{0z}	-	free space vector Green's function with a source pointed in the z direction.
\tilde{I}	-	unit dyad or idem factor.
PV	-	principal value.
V	-	cell volume.
N	-	number of cell.
V_m	-	volume in cell m .
V_n	-	volume in cell n .
a_n	-	cell radius.
m	-	field cell.
n	-	source cell.
p, q	-	$= 1, 2$ and 3 indicated x, y and z respectively.
R_{mn}	-	distance between cell m and n .
\vec{r}_m	-	field point.

\vec{r}_n	-	source point.
α_{mn}	-	$k_0 R_{mn}$
$\cos \theta_{x_p}^{mn}$	-	$\frac{x_p^m - x_p^n}{R_{mn}}$
$\cos \theta_{x_q}^{mn}$	-	$\frac{x_q^m - x_q^n}{R_{mn}}$
$e^{j\omega t}$	-	time factor.
η	-	wave intrinsic impedance.
η_0	-	free space wave intrinsic impedance.
E_x	-	electric field in the positive x -direction.
H_y	-	electric field in the positive y -direction.
E-field	-	electric field.
H-field	-	magnetic field.
EM	-	electromagnetic.
E_{n1}	-	normal component of electric field in medium 1.
E_{n2}	-	normal component of electric field in medium 2.
ϵ_1	-	permittivity of material 1.
ϵ_2	-	permittivity of material 2.
E_{t1}	-	tangential component of electric field in medium 1.
E_{t2}	-	tangential component of electric field in medium 2.
\hat{n}	-	unit normal.
v	-	velocity of propagation in free space.

r	-	distance.
h	-	distance from cellular phone to observation point.
L	-	largest dimension of antenna.
E_0	-	electric field amplitude.
H_0	-	magnetic field amplitude.
λ	-	wavelength.
k_0	-	free space wave number.
k	-	wave number.
k_n	-	wave number of n th dielectric.
P_i	-	incident power density.
z	-	distance from antenna along z -axis.
z_0	-	distance from antenna to material surface in free space along z -axis.
z_n	-	distance between two material along z -axis.
α	-	attenuation constant.
δ	-	skin depth.
$\tan \delta$	-	loss factor or dissipation factor.
\exp	-	exponent.
\hat{x}	-	unit vector in the positive x -direction.
\hat{y}	-	unit vector in the positive y -direction.
\hat{z}	-	unit vector in the positive z -direction.
W	-	Watt.

W/kg	-	Watt/kilogram.
g	-	gram.
F/m	-	Farads/meter.
H/m	-	Henrys/meter.
A/m	-	Amperes/meter.
C/m ²	-	Coulombs/meter ² .
Weber/m ²	-	Webers/meter ² .
A/m ²	-	Amperes/meter ² .
C/m ³	-	Coulombs/meter ³ .
S/m	-	Siemens/meter.
rad/s	-	Radians/second.
V/m	-	Volt/meter.
m	-	Meter.
m ⁻¹	-	permeter.
kg/m ³	-	Kilogram/meter ³ .
W/m ²	-	Watt/meter ² .
cm	-	centimeter.
J	-	complex value (FORTRAN language).
KO	-	free space wave number (FORTRAN language).
EPSO	-	free space permittivity (FORTRAN language).
UO	-	free space permeability (FORTRAN language).
M	-	field cell – particular cell (FORTRAN language).
N	-	source cell – all cell (FORTRAN language).
NCELL	-	number of cell (FORTRAN language).

MXCLL	-	maximum number of cell (FORTRAN language).
MXCLL3	-	maximum dimension coefficient matrix (FORTRAN language).
F	-	frequency of cell N (FORTRAN language).
W	-	angular frequency of cell N (FORTRAN language).
X(1,N)	-	x component of cell N (FORTRAN language).
X(2,N)	-	y component of cell N (FORTRAN language).
X(3,N)	-	z component of cell N (FORTRAN language).
V(N)	-	volume of cell N (FORTRAN language).
SIGMA(N)	-	conductivity of cell N (FORTRAN language).
EPS(N)	-	permittivity of cell N (FORTRAN language).
RHO(N)	-	density of cell N (FORTRAN language).
TAU(N)	-	array storing value of cell N (FORTRAN language).
S(N)	-	mass of cell N (FORTRAN language).
X(1,M)	-	x component of cell M (FORTRAN language).
X(2,M)	-	y component of cell M (FORTRAN language).
X(3,M)	-	z component of cell M (FORTRAN language).
DIST	-	distance between cell M and N (FORTRAN language).
EI(N)	-	concatenated matrix of incident electric field (FORTRAN language).
EIR(N)	-	real part of incident electric field (FORTRAN language)
EIR(N)	-	imaginary part of incident electric field (FORTRAN language)
E(N)	-	concatenated matrix of induced electric field (FORTRAN language)
G	-	coefficient matrix (FORTRAN language).

X1	-	row location in G-matrix (FORTRAN language).
X2	-	column location in G-matrix (FORTRAN language).
P	-	= 1, 2 and 3 represent x, y and z respectively (FORTRAN language).
Q	-	= 1, 2 and 3 represent x, y and z respectively (FORTRAN language).
POW(N)	-	absorbed power in cell N (FORTRAN language).
SAR(N)	-	SAR in cell N (FORTRAN language).
AVSAR(N)	-	averaged SAR in cell N (FORTRAN language).
A	-	concatenated matrix (FORTRAN language).
IRMAX	-	maximum row dimension of A and X matrix (FORTRAN language).
IRMAX1	-	maximum column dimension of A matrix (FORTRAN language).
N	-	actual row dimension (FORTRAN language).
M	-	actual column dimension (FORTRAN language).
X	-	output G-Matrix (FORTRAN language).
ITMA	-	Institute of Advanced Technology.
FSAS	-	Faculty of Science and Environmental Studies.

CHAPTER 1

INTRODUCTION

1.1 Introduction

Beginning in 1950s, wireless communication services become a major consumer in paging and cellular telephony. Since then, both services dominated in consumer marketplace. At the end of 1994, paging and cellular telephone had grown to a worldwide market serving 50 million and 52 million users representing a growth rate of 40% and 58% respectively [1].

In most developing countries, cellular phone is emerging as the wireless technology of choice for basic telephone service. With the growth of the cellular phone usage and design, it becomes a necessity to have a rapid and precise method to calculate and measure the electromagnetic field in human tissue.

A number of key market and technology forces are driving the growth in the wireless communications. They can be summarized as follows:

1. The demand to improve productivity, safety communication, responsiveness and the quality of life that wireless communication can provide.
2. The shift to global economy as well as the changing and political scene in international markets has opened up new opportunities for all technologies.